

Agri-Vac

6614



WALINGA
INC.

TOUGH TO BEAT IN THE LONG RUN



**SPECIFICATIONS FOR:
Walinga Pneumatic Grain Moving Unit Model 6614**

	6614 PC	6614 DLX
HEIGHT	95" (241 cm)	95" (241 cm)
WIDTH	92" (234 cm)	92" (234 cm)
LENGTH	105" (267 cm)	105" (267 cm)
WEIGHT	2814 lbs (1279 kg)	3014 lbs (1370 kg)
DISCHARGE HEIGHT	15.3'(4.7m) maximum - 8"(0.2m) minimum	15.3'(4.7m) maximum - 8"(0.2m) minimum
HP REQUIRED	110-130 hp	110-130 hp
PTO SPEED	1000 RPM	1000 RPM
LINE SIZE	5" (125 mm) & 6" (150 mm)	5" (125 mm) & 6" (150 mm)
TIRES	Two standard farm implement	Two standard farm implement
WHEELS	15" (38 cm), 5 stud	15" (38 cm), 5 stud
BLOWER	#614 Walinga SRT (Sound Reduction Type), CORVOR™ Hard Coating, Positive Displacement Blower	#614 Walinga SRT (Sound Reduction Type), CORVOR™ Hard Coating, Positive Displacement Blower
AIRLOCK	#1618 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation	#1618 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation
DRIVE	Tongue mounted drive shaft with V-type 5 groove sheaves & belts	Tongue mounted drive shaft with V-type 5 groove sheaves & belts
HYDRAULICS	Hoses & quick couplings Open/closed centre system	Self Contained
RECEIVER	28" dia. (71 cm) two piece, single inlet	28" dia. (71 cm) two piece, dual inlets
PRECLEANER	24" dia. (61 cm)	24" dia. (61 cm)
SAFETY	Vacuum/Pressure relief valves	Vacuum/Pressure relief valves

6614 & 6614 DLX

CAPACITY*	Bu/hr*	Tonnes/hr*
Corn & Barley	3600	92
Wheat	3200	84
Soybeans	2800	75

Due to continuous product development, specifications are subject to change without notice. Some items shown may be optional.
*Capacities based on using 12' (3.65 m) suction line and truck loading kit.
Capacity will vary with condition of product.

6614

AVAILABLE OPTIONS

- Hydraulic Boom Rotation
- Dual inlets on 6614
- Self contained hydraulics on 6614
- Full Rhino Lined Receiver Tank & boom cyclone
- CORVOR™ Hard Coated Airlock
- Stainless steel delivery lines



STANDARD ACCESSORIES

- Hose carrier
- Precleaner on 6614
- Walinga SRT (Sound Reduction Type) Positive Displacement CORVOR™ Hard Coated Blower
- Hydraulic-rotating truck loading kit with cyclone
- Two 6" dia. x 12' (150 mm x 3.65 m) galvanized steel delivery lines (DLX model comes with Stainless Steel Hoses)
- One 6" dia. (150 mm) suction nozzle
- One 6" dia. x 12' (150 mm x 3.65 m) rubber clean-up hose with swivel coupling
- One 6" dia. (150 mm) suction nozzle with clean-up attachment floor sweep with wheels
- Rhino liner covering high wear areas in receiver tank and boom cyclone



Suction Nozzle

Floor Sweep Nozzle

6614 REAR VIEW

WALINGA.COM

Head Office

R.R. #5,
Guelph, Ontario
Canada N1H 6J2
Tel: 519.824.8520
Tel: 888.925.4642
Fax: 519.824.5651

Michigan

1190 Electric Ave.
Wayland, Michigan
USA 49348
Tel: 616.877.3470
Tel: 800.466.1197
Fax: 616.877.3474

Manitoba

70 3rd Ave. N.E.
Box 1790
Carman, Manitoba
Canada R0G 0J0
Tel: 204.745.2951
Fax: 204.745.6309

Ontario

938 Glengarry Cres.
Fergus, Ontario
Canada N1M 2W6
Tel: 519.787.VACS (8227)
Fax: 519.787.8210

Australia

Customvac Australia
24 Molloy St.
Toowoomba Qld 4350
Australia
Tel: 1800 242 699

