

TECHNICAL BULLETIN



Subject:

FOOD GRADE LUBRICANTS FOR BLOWER & A/L

Bulletin #:	Rev:	Created by:	Date:		
155435	A	LNJ	2024-08-23		
ECR #:	Department:	Engineering: ✓	Production: ✓	Service: ✓	Sales: ✓
149622	Product Lines:	Transportation Equipment: ___	Pneumatic Equipment: ✓		

To accommodate applications in which a customer is conveying a product that must meet the Food Grade standards, specialised lubricants for the blower and airlock are required.

For Food Grade blowers, the standard Walinga Blower Oil (98-19152-6) must be replaced with the Food Grade compliant gear oil. Food Grade blowers must use **98-133710-6** (PURITY FG SYN EP GEAR FLUID 20L).

For Food Grade airlocks, the standard grease (98-14436-6) must be replaced with the Food Grade compliant grease. Food Grade airlocks must use **98-133711-6** (PURITY FG2 EXTREME 17 KG PAIL).

Several assemblies have been specifically configured for Food Grade applications to include the required lubricants in their respective Bill of Materials. These assemblies are as follows:

510 Blower	43-137976-5	<i>BLOWER, 510, CHR, 7.25", TIGHT, FG</i>
1314 Airlock	43-137975-5	<i>A/L, 1314DT, FXR, HXS TIP, FG</i>

If you require Food Grade lubricants for your Walinga equipment, please contact your regional Walinga sales representative.